

INVERSOR POWER INVERTER A301 - 150 W

ITEMS	DC12V	DC24V
OUTPUT POWER	150W CONTINUE 300W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10~15 v	DC 20~30 V
OUTPUT VOLTAGE	AC 100 V, 110 V, 120 V, 220 V, 230 V, 240 V	
OUTPUT VOLTAGE REGULATION	+/- 5 %	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
BATTERY LOW SHUTDOWN	DC 10+/- 0.5V	DC 20 +/- 0.8 V
BATTERY LOW SHUTDOWN	DC 9.5 +/- 0.5 V	DC 19.5 +/- 0.8 V
STANDBY CURRENT	0.2A	0.2A
EFFICIENCY	90%	
THERMAL PROTECT	60 +/- 0.5oC	
COOLING	BY AIR CONVECTION	
PROTECTIONS	SOFT START OUTPUT SHORT : SHUTDOWN INPUT POLARITY REVERSE : BY FUSE HIGH VOLTAGE INPUT : SHUTDOWN LOW VOLTAGE INPUT : SHUTDOWN ✖ OVERLOAD : SHUTDOWN OVERTEMPURTURE : SHUTDOWN AFTER BUZZER KEEP SOUNDING FOR ONE MINUTE BATTERY LOW : ALARM TROUBLE DISPLAY : LED	
FUSE	15 A	10 A
AC OUTLET	ONE AC OUTLET	
SIZE (LxWxH)	122x77x45 mm (TYPE 1, 2) 122x77x70 mm (THE OTHER)	
WEIGHT	0.45 kgs 0.55 kgs	

