

INVERSOR POWER INVERTER A301 - 300 W

ITEMS	DC12V	DC24V
OUTPUT POWER	300W CONTINUE 350W (30 MIN) 600W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10~15 v	DC 20~30 V
OUTPUT VOLTAGE	AC 100 V,110 V,120 V,220 V,230 V,240 V	
OUTPUT VOLTAGE REGULATION	+/- 5 %	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
BATTERY LOW ALARM	DC 10+/- 0.5V	DC 20 +/- 0.8 V
BATTERY LOW SHUTDOWN	DC 9.5 +/- 0.5 V	DC 19.5 +/- 0.8 V
STANDBY CURRENT	0.36A	0.2A
EFFICIENCY	90%	
THERMAL PROTECT	60 +/- 0.5oC	
COOLING	WISDOM FAN START : WHEN THE OUTPUT REACH 100W THE TEMPERTURE REACH 40°C, THE FAN WILL START AUTOMATICALLY	
PROTECTIONS	SOFT START OUTPUT SHORT : SHUTDOWN INPUT POLARITY REVERSE : BY FUSE HIGH VOLTAGE INPUT :SHUTDOWN LOW VOLTAGE INPUT : SHUTDOWN OVERLOAD : SHUTDOWN OVERTEMPERTURE : SHUTDOWN AFTER BUZZER KEEP SOUNDING FOR ONE MINUTE BATTERY LOW : ALARM INTELLIGENT FAN CONTROL TROUBLE DISPLAY : LED	
FUSE	CIGARETTE PLUG : 15 A BATTERY CORD : 35 A	CIGARETTE PLUG : 10 A BATTERY COR : 20 A
AC OUTLET	TWO AC OUTLET (TYPE 1,2) ONE AC OUTLET (THE OTHER)	
SIZE (LxWxH)	165x88x74 mm	
WEIGHT	0.9 kgs	

