

# INVERSOR POWER INVERTER A301 - 800 W

ITEMS	DC12V	DC24V
OUTPUT POWER	800W CONTINUE 2000W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10~15 V	DC 20~30 V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V	
OUTPUT VOLTAGE REGULATION	+/- 5%	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
BATTERY LOW ALARM	DC 10+/- 0.5V	DC 20+/- 0.8V
BATTERY LOW SHUTDOWN	DC 9.5 +/- 0.5 V	DC 19.5 +/- 0.8 V
STANDBY CURRENT	< 0.5A	< 0.4A
EFFICIENCY	85~90%	
THERMAL PROTECT	60 +/- 0.5°C	
COOLING	WISDOM FAN START : WHEN THE OUTPUT REACH 250W THE TEMPERTURE REACH 40°C, THE FAN WILL START AUTOMATICALLY	
PROTECTIONS	SOFT START OUTPUT SHORT : SHUTDOWN INPUT POLARITY REVERSE : BY FUSE HIGH VOLTAGE INPUT : SHUTDOWN LOW VOLTAGE INPUT : SHUTDOWN OVERLOAD : SHUTDOWN OVERTEMPATURE : SHUTDOWN AFTER BUZZER KEEP SOUNDING FOR ONE MINUTE BATTERY LOW : ALARM INTELLIGENT FAN CONTROL TROUBLE DISPLAY : LED	
FUSE	25 A x 4	20 A x 4
AC OUTLET	TWO AC OUTLET (TYPE 1,2) ONE AC OUTLET (THE OTHER)	
SIZE (LxWxH)	280 x 200 x 70 mm	
WEIGHT	2.6 kgs	

